


**NOTES:**

1. HE LEAK TEST @ 1 ATM. <10<sup>-6</sup> -5 CC/S.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. FINISH APPLIES TO SPOTFACE FOR O-RING SEAL ONLY.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

6	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
5	A/R	PAVE-Seal 150	EPOXY BLACK
4	1	0183	NUT VS15-SS
3	1	-215 VITON	O-RING -215 VITON 75
2	1	0161	HOUSING VS15L-SS
1	73.5'	RXT20	CABLE T/C 20 TYPE RX TEFLON PFA
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 X DECIMAL +/- .1 XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pave-technology.co

DESCRIPTION: PAVE-Seal/E Cable Harnesses  
**VS15L-SS-150-9P-RXT20-48-48**

PART NUMBER: **1875**

PROJECTION: 