


NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 7.5 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 M .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.


3	8	TT27	CABLE T/C TYPE T 27AWG TEFLON
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0346	HOUSING PT8-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION *PAVE-Seal® Cable Harnesses*
PT8-SS-150-8P-TT27-84-96

PART NUMBER 1944	PROJECTION 
----------------------------	---