



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-6} CC/S.
2. HYPOT 630 VDC 500 M .01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.
5. WIRE COLOR ARRANGEMENTS ARE RANDOM.

6	7@35"	E28 ORANGE	WIRE 28E MIL-W-16878/4 .010 7/#36
5	7@35"	E28 RED	WIRE 28E MIL-W-16878/4 .010 7/#36
4	6@35"	E28 WHITE	WIRE 28E MIL-W-16878/4 .010 7/#36
3	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
2	1	-016 VITON	O-RING -016 VITON 75
1	1	0130	HOUSING SPF12-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION	SPF12-E-150-20-TE28-24-10	
PART NUMBER	1947	PROJECTION