



**NOTES:**

1. HE LEAK TEST @1 ATM. <math>10^{-6}</math> CC/S.
2. HYPOT 630 VDC 500 M .01 SEC MINIMUM, PIN TO PIN & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

9	1	SC3116F8-3S	PLUG 3 #20 SOCKETS
8	1	SC3116F8-3P	PLUG 3 #20 PINS
7	1	0183	NUT VS15-SS
6	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
5	1	-215 VITON	O-RING -215 VITON 75A
4	A/R	PAVE-Seal 150	EPOXY BLACK
3	1	0161	HOUSING VS15L-SS
2	1	SC3112E8-3S	RCPT 3 #20 SOCKETS
1	1	SC3112E8-3P	RCPT 3 #20 PINS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Mate® I Connectors  
 VS15L-SS-150-3-20-3112PS

PART NUMBER  
 1956

