



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-6} CC/S.
2. HYPOT 630 VDC 500 M .01 SEC MINIMUM, PIN TO PIN.
3. CONTINUITY TEST W/MATING PLUGS <math><1.0</math> W
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

7	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
6	1	-231 VITON	O-RING -231 VITON 75
5	A/R	PAVE-Seal 150	EPOXY BLACK
4	1	SC3102A32-7S	RCPT 28 #16 & 7 #12 SOCKETS
3	1	SC3102A32-7P	RCPT 28 #16 & 7 #12 PINS
2	1	0102	NUT VS32-SS
1	1	0318	THREAD INSERT VS32-SS

ITEM	QTY	PART#	DESCRIPTION
------	-----	-------	-------------

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Mate® I Connectors
VS32-E-150-28/7-16/12-3102PSNP

PART NUMBER
1958

