



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-6} CC/S WITH 1954 LTP.
2. HYPOT 630 VDC 500 M .01 SMC MINIMUM, WIRE TO WIRE & HOUSING WITH 1933 ETF.
3. FINISH FOR SPOTFACE ON O-RING SEAL AREA.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

6	1	0102	NUT VS32-SS
5	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
4	1	-231 VITON	O-RING -231 VITON 75
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	2	50RIB	CABLE 50 #26 RIBBON
1	1	0101	HOUSING VS32-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses
VS32-SS-150-2-50RIB-4-26

PART NUMBER **1961**

PROJECTION