



NOTES:

1. LEAK TEST: 9000 PSI, NO BUBBLES 1 MINUTE MINIMUM.
2. OPTICAL CONTINUITY CHECK END TO END W/ FLASHLIGHT.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

6	3@54mm	STT-30-50	TUBING TEFLON
5	1	-012 TEFLON	RING -012 TEFLON BACKUP SINGLE TURN SCARF CUT
4	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM
3	2	-012 BUNA	O-RING -012 BUNA 75
2	3@1m	1993	FIBER OPTIC SINGLE MODE DEPRESSED CLADDING
1	A/R	PAVE-Seal 150	EPOXY BLACK
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN MM
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/--.13
 X.X DECIMAL +/-2.5 X.XX DECIMAL +/-0.50 X.XXX DECIMAL +/-0.100
 ANGLES +/- 1 DEG SURFACE FINISH 3.2 micrometers RMS



DESCRIPTION *PAVE-Opti SealFromans.shx; Cable Harnesses*
SP8H-E-150-3-FO-0.5-0.5m

PART NUMBER
1991

REVISION LEVEL **A**
 PROJECTION