



- NOTES:
1. HE LEAK TEST @ 1 ATM. 10^{-7} CC/S.
 2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

7	A/R	PAVE-Seal 150	EPOXY BLACK
6	1	-215 VITON	O-RING -215 VITON 75
5	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
4	1	0183	NUT VS15-SS
3	6@41"	KT20	EPOXY BLACK
2	2@41"	RXT20, RX/SX	CABLE T/C 20 ANSI BX TWSH
1	1	0161	HOUSING VS15L-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE Technology Co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses
VS15L-SS-150-2P/6P-RT20/KT20-36-3

PART NUMBER
2038

PROJECTION