


NOTES:

1. LEAK TEST: 200 PSI, NO BUBBLES 3 MINUTES MINIMUM.
2. HYPOT 1000VAC, WIRE TO WIRE & HOUSING IN SALT WATER.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

6	1	24/C#18TJP	CABLE 12TP/#18 W/OAJ 1"OD 507FT MINIMUM
5	A/R	EN-1556 BLACK	URETHANE BLACK
4	A/R	PAVE-Seal 150HV	EPOXY BLUE HIGH VOLTAGE
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
2	1	-941 BUNA	O-RING -941 BUNA 75
1	1	2069	HOUSING SO26L-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**
SO26L-SS-150HV-1-CABLE-500FT-6FT

PART NUMBER **2045**

PROJECTION 