



- NOTES:
1. HE LEAK TEST @1 ATM. $<10^{-7}$ CC/S AIR EQUIVALENT. (AIR EQUIVALENT LEAK RATE/2.73 = ACTUAL He LEAK RATE)
 2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
 3. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
 4. THESE SPECIFICATIONS SUPERSEDE PAVE CATALOG.

7	1	SUPER O-LUBE	LUBRICANT O-RING SILICONE BASED
6	A/R	PAVESEAL 150	EPOXY BLACK
5	1	SC3102A18-12S	RCPT 6 #16 SOCKET
4	1	SC3102A18-12P	RCPT 6 #16 PIN
3	1	-224 VITON	O-RING -224 VITON 75
2	1	0199	NUT VS22-SS
1	1	0189	HOUSING VS22-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology 2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)690-1100
fax (937)690-5165
www.pavetechnologyco.com

DESCRIPTION
VS22-SS-150-6-16-3102PS(NP)

PART NUMBER
2059

PROJECTION