



- NOTES:
1. LEAK TEST: 150 PSI, NO BUBBLES 1 MINUTE MINIMUM.
  2. HYPOT 200 VDC 100 MW .01 SEC MINIMUM, WIRE TO WIRE & THREADS.
  3. FINISH FOR SPOTFACE ON O-RING SEAL AREA.
  4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
  5. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

6	1	0102	NUT VS32-SS
5	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED
4	1	-231 SILICONE	O-RING -231 SILICONE 70
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	2	PVC34/C#28RIB	CABLE 34 #28 PVC RIBBON
1	1	0318	THREAD INSERT VS32-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN MM  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-13  
 .X DECIMAL +/- 2.5 .XX DECIMAL +/- .50 .XXX DECIMAL +/-100  
 ANGLES +/- 1 DEG SURFACE FINISH 3.2 micrometers RMS

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**  
**VS32-E-150-2-34RIB-150-350mm**

PART NUMBER **2083**

PROJECTION