



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-7} CC/S.
2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
3. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.
4. REF - MAX TEMPERATURE 80°C.

3	A/R	PAVE-Seal 80	EPOXY BLACK
2	1	PC-BOARD	PCB POSITION SENSOR ARM ANGLE
1	1	SENSOR-BIT	HOUSING FP14-AL
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION PAVE-Flex® Cable Harnesses
FP14-AL-80-1-PCB-2-1

PART NUMBER **2110**

PROJECTION