



NOTES:

1. HE LEAK TEST @1 ATM. <10⁻⁷ CC/S AIR EQUIVALENT.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING. IDC (INSULATION DISPLACEMENT CONNECTOR) MARKS OK PAST 12" MINIMUMS.
3. REF IDCs: T & B/ANSLEY 636-25SM & 636-25PM.
4. ITEM 6 POSITIONS ARE APPROXIMATELY AS SHOWN.
5. REF-É"3.0 MIN SPOTFACE FINISH.
6. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
7. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

6	8x2.3 FT	BEL# 8R28025	CABLE RIBBON 25 FEP28 RAINBOW
5	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE BASED
4	1	-231 VITON	O-RING -231 VITON 75
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	1	0102	NUT VS32-SS
1	1	0101	HOUSING VS32-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 micron RMS



DESCRIPTION PAVE-Seal/E Cable Harnesses
 VS32-SS-150-8R25-TE28-12-12

PART NUMBER

2118

PROJECTION

