


NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 4 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE, SHIELD & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

3	A/R	PAVE-Seal 200	EPOXY BLACK
2	9@98°	KF22	CABLE T/C TYPE K 22AWG
1	1	2148	HOUSING PT20-SS 316SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 X DECIMAL +/- .1 XX DECIMAL +/- .02 XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937) 690-1100
fax (937) 690-5165
www.pavetechnologyco.com

DESCRIPTION PAVE-Seal/E Cable Harnesses
PT20-SS-200-9P-KF22-48-48

PART NUMBER	PROJECTION
2125	