



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 8 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MΩ .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. FINISH APPLIES TO SPOTFACE FOR O-RING SEAL ONLY.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

6	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE BASE
5	1	-215 VITON	O-RING -215 VITON 75
4	1	0183	NUT VS15-SS
3	9x196	KT24	CABLE T/C TYPE K 24AWG TEFLON
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0161	HOUSING VS15L-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co. 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION *PAVE-Seal@ Cable Harnesses*
VS15L-SS-150-9P-KT24-96-96
 PART NUMBER **2129**
 REVISION LEVEL -
 PROJECTION