


NOTES:


1. HE LEAK TEST @1 ATM. 10×10^{-8} CC/S OR LESS.
2. HIPOT 630 VDC 500 MΩ .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. FINISH APPLIES TO SPOTFACE FOR O-RING SEAL ONLY.
6. DIMENSIONS ARE INCHES [millimeters].
7. NO VOIDS LARGER THAN $\phi 0.035$ [0.89] ARE ACCEPTABLE.
8. REF - OPERATING TEMPERATURE RANGE: -20 TO 125°C.
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

3	A/R	PAVE-Seal 150	EPOXY BLACK
2	1	3354	HOUSING PT4-B
1	2	TT24	CABLE T/C TYPE T#24 TEFLON
ITEM	QTY	PART#	DESCRIPTION


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION *PAVE-Seal® Cable Harnesses*
PT4-B-150-2P-TT24-16-X

PART NUMBER *SEE TABLE*
2136

REVISION LEVEL **C**
 PROJECTION 

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS