


NOTES:

1. HE LEAK TEST @1 ATM. 10^{-8} CC/S, USING -338 O-RING (NOT INCLUDED), LUBED W/ SUPER O-LUBE.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & FLANGE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

3	A/R	PAVE-Seal 150	EPOXY BLACK
2	12	KG20	CABLE T/C TYPE K 20AWG GLASS
1	1	2158	HOUSING FL-SS 6" 4BH
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)890-1100
fax (937)890-5165
www.pave-technology.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**
FL-SS-150-12P-KG20-96-36

PART NUMBER **2145**

PROJECTION 