



**NOTES:**

1. HE LEAK TEST @1 ATM. <math>10^{-5}</math> CC/S.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

7	4@50"	E16 WHITE	WIRE 16E MIL-W-16878/4 .010 19/#29
6	4@50"	E16 RED	WIRE 16E MIL-W-16878/4 .010 19/#29
5	4@50"	E16 ORG	WIRE 16E MIL-W-16878/4 .010 19/#29
4	4@50"	E16 GRAY	WIRE 16E MIL-W-16878/4 .010 19/#29
3	4@50"	E16 BLUE	WIRE 16E MIL-W-16878/4 .010 19/#29
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	1625	HOUSING PT16-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses  
 PT16-SS-200-20-TE16-24-24

PART NUMBER  
 2149

PROJECTION

