



2151-1	48 [1220]
2151	24 [610]
PAVE#	X

12	3	E20 YELLOW	WIRE 20E MIL-W-16878 .010 7/28
11	3	E20 WHITE	WIRE 20E MIL-W-16878 .010 7/28
10	3	E20 VIOLET	WIRE 20E MIL-W-16878 .010 7/28
9	3	E20 RED	WIRE 20E MIL-W-16878 .010 7/28
8	3	E20 ORG	WIRE 20E MIL-W-16878 .010 7/28
7	3	E20 GREEN	WIRE 20E MIL-W-16878 .010 7/28
6	3	E20 GRAY	WIRE 20E MIL-W-16878 .010 7/28
5	3	E20 BROWN	WIRE 20E MIL-W-16878 .010 7/28
4	3	E20 BLUE	WIRE 20E MIL-W-16878 .010 7/28
3	3	E20 BLACK	WIRE 20E MIL-W-16878 .010 7/28
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	1625	HOUSING PT16-SS
ITEM	QTY	PART#	DESCRIPTION

NOTES:

1. HE LEAK TEST @1 ATM. $<10^{-5}$ CC/S.
2. HYPOT 630 VDC 500 MΩ .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal@ Cable Harnesses
 PT16-SS-200-30-TE20-X-X

PART NUMBER
 2151

REVISION LEVEL
 A
 PROJECTION