

- NOTES:**
1. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE.
  2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	2030032-01	MICRO-D PLA SUPP
ITEM	QTY	PART#	DESCRIPTION



ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE will meet the assembly and test specifications of the customer as documented on this assembly drawing. Any changes must be approved by PAVE.



2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION  
**MIRCOD-E-150-21-TZ30-7-0**

PART NUMBER <b>2191</b>	PROJECTION  
----------------------------	---