



- NOTES:
1. HE LEAK TEST @1 ATM. 10^{-7} CC/S AIR EQUIVALENT.
 2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
 3. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
 4. THERMAL CYCLE 25°C TO 200°C W/ 1/2 HOUR HOLD @ TEMP BEFORE LEAK TESTING.
 5. WIRE POSITIONS & ARRANGEMENTS ARE VARIABLE.

15	3@40.2'	E20 YELLOW	WIRE 20E MIL-W-16878 .010 7/28
14	3@40.2'	E20 WHITE	WIRE 20E MIL-W-16878 .010 7/28
13	3@40.2'	E20 VIOLET	WIRE 20E MIL-W-16878 .010 7/28
12	3@40.2'	E20 RED	WIRE 20E MIL-W-16878 .010 7/28
11	2@40.2'	E20 ORG	WIRE 20E MIL-W-16878 .010 7/28
10	2@40.2'	E20 GREEN	WIRE 20E MIL-W-16878 .010 7/28
9	2@40.2'	E20 GRAY	WIRE 20E MIL-W-16878 .010 7/28
8	2@40.2'	E20 BROWN	WIRE 20E MIL-W-16878 .010 7/28
7	2@40.2'	E20 BLUE	WIRE 20E MIL-W-16878 .010 7/28
6	2@40.2'	E20 BLACK	WIRE 20E MIL-W-16878 .010 7/28
5	1	0185	NUT VS26-SS
4	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE BASED
3	1	-226 VITON	O-RING -226 VITON 75
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	1531	HOUSING VS26-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses
 VS26-SS-200-24-TE20-240-240

PART NUMBER

2204

PROJECTION

