



10	A/R	PAVE-Seal 150	EPOXY BLACK
9	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
8	1	-215 VITON	O-RING -215 VITON 75
7	1	0183	NUT VS15-SS
6	1@8.50'	EE22 MIL RED	WIRE 22EE MIL-W-16878 7/#30
5	1@8.50'	EE22 MIL GRAY	WIRE 22EE MIL-W-16878 7/#30
4	1@8.50'	EE22 MIL BLUE	WIRE 22EE MIL-W-16878 7/#30
3	1@8.50'	EE22 MIL BLK	WIRE 22EE MIL-W-16878 7/#30
2	6@8.50'	TT20	CABLE T/C TYPE T #20 TEFLON FEP
1	1	0161	HOUSING VS15L-SS
ITEM	QTY	PART#	DESCRIPTION

NOTES:

1. HE LEAK TEST @ 1 ATM. 10^{-7} CC/S.
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. WIRE COLOR POSITIONS MAY VARY.

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses
 VS15L-SS-150-6P/4-TT20/EE22-48-48

PART NUMBER
 2214

