



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 4 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE, SHIELD & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

| 3 | A/R | PAVE-Seal 200 | EPOXY BLACK |
|------|-------|---------------|------------------------|
| 2 | 5@98" | KF22 | CABLE T/C TYPE K 22AWG |
| 1 | 1 | 2148 | HOUSING PT20-SS 316SS |
| ITEM | QTY | PART# | DESCRIPTION |

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)890-1100
fax (937)890-5165
www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION **PAVE-Seal® Cable Harnesses**
PT20-SS-200-5P-KF22-48-48

PART NUMBER **2234**

PROJECTION