



PART #	(X)	Y	Z	NETWOCO #	W
2253	7	10.3	17.3	900729	50
2253-1	12	17.5	29.5	90072902	75

NOTES:
 1. HE LEAK TEST 10% OF PARTS @1 ATM. <10⁻⁶ CC/S.
 2. CHECK OPTICAL CONTINUITY.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 4. ITEMS 3 THRU 5 CUSTOMER SUPPLIED.
 5. HANDLE ITEMS 3 THRU 5 CAREFULLY-1" DIA MIN COIL GLASS FIBER BREAKS WHEN BENT SHARPLY.
 6. REAPPLY PLASTIC CAPS TO TERMINALS DURING HANDLING.

8	1	0894	NUT VS8-SS
7	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE BASED
6	1	-112 BUNA	O-RING -112 BUNA 75
5	Z SEE TABLE	7120555-40-2050R	SMFO FC/UPC to LC/UPC WCM RED
4	Z SEE TABLE	7120555-40-2050W	SMFO FC/UPC to LC/UPC WCM WHITE
3	Z SEE TABLE	7120555-40-2050B	SMFO FC/UPC to LC/UPC WCM BLUE
2	A/R	PAVE-Seal	EPOXY BLACK
1	1	2265	HOUSING VS8-AL
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Opti SealFromans.shx; Cable Harnesses
 VS8-AL-150-3-FOSMF28-7-10

PART NUMBER 2253 PROJECTION