



- NOTES:**
1. HE LEAK TEST @1 ATM. 10^{-6} CC/S.
 2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

5	A/R	PAVE-Seal 150	EPOXY BLACK
4	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE-BASED
3	1	-924 VITON	O-RING -924 BUNA 75
2	1	0643	HOUSING SO26-SS
1	674'	TT20	CABLE T/C TYPE T#20 TEFLON
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE Technology Co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal® Cable Harnesses**
SO26-SS-150-40P-TT20-100-100

PART NUMBER **2372**

PROJECTION