



- NOTES:
1. HE LEAK TEST @ 1 ATM. 10^{-6} CC/S.
 2. HYPOT 15,000 VDC 5mA MAX LEAKAGE WIRE TO LEAK TEST PORT.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

4	0.8m	BELDEN 8868	WIRE 22HV 7#30 24KVDC
3	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE-BASED
2	2	-015 VITON 70	O-RING -015 VITON 70
1	1	1374	HOUSING SP11L-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN MM
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .13
 .X DECIMAL +/- 2.5 .XX DECIMAL +/- .50 .XXX DECIMAL +/- .100
 ANGLES +/- 1 DEG SURFACE FINISH 3.2 micrometers RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE Technology Co.

DESCRIPTION *PAVE-Seal® Cable Harnesses*
SP11L-E-150-1-B8868-60-20CM

PART NUMBER
2392

PROJECTION