



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, CONTACTS TO CONTACTS & HOUSING W/MATING PLUGS.
3. CONTINUITY <1 W PIN TO SOC.
4. EQUIVALENTS FOR LISTED ITEMS MAY BE USED.
5. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

4	A/R	PAVE-Seal 150	EPOXY BLACK
3	1	16-12RB-B	HOUSING PT16-B
2	1	SC3112E14-18S	RCPT 18#20 SOC
1	1	SC3112E14-18P	RCPT 18#20 PIN
ITEM	QTY	ITEM#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
Dayton, Ohio 45414-3445
U.S.A.
(937)890-1100
Fax (937)890-5165
www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses

PT16-B-80-18-20-3112PS(NP)

PART NUMBER	PROJECTION
2398	