



- NOTES:
 1. HE LEAK TEST @ 1 ATM. 10^{-8} CC/S.
 2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, PIN TO PIN.
 3. CONTINUITY TEST W/MATING PLUGS <math><1.0</math> W.
 4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 5. ITEMS 3 & 4, NOT SHOWN, TO BE SHIPPED W/ PART.

9	1	1531	HOUSING VS26-SS
8	1	0185	NUT VS26-SS
7	A/R	PAVE-Seal 150	EPOXY BLACK
6	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
5	1	-226 VITON	O-RING -226 VITON 75
4	1	SC3126F22-21S	PLUG 21 #16 SOCKETS
3	1	SC3126F22-21P	PLUG 21 #16 PINS
2	1	SC3112E22-21S	RCPT 21 #16 SOCKETS
1	1	SC3112E22-21P	RCPT 21 #16 PINS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Mate® I Connectors
 VS26-SS-150-21-16-3112PS

PART NUMBER
 2402

PROJECTION

