



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-7} CC/S.
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ASSEMBLY TO SHIP W/ COPPER GASKET (ITEM 2).

13	6@16'	E22 WHT/BLU	WIRE 22E MIL-W-16878/4 .010 7/#30
12	6@16'	E22 WHT	WIRE 22E MIL-W-16878/4 .010 7/#30
11	6@16'	E22 VIOLET	WIRE 22E MIL-W-16878/4 .010 7/#30
10	6@16'	E22 RED	WIRE 22E MIL-W-16878/4 .010 7/#30
9	6@16'	E22 ORANGE	WIRE 22E MIL-W-16878/4 .010 7/#30
8	6@16'	E22 GREEN	WIRE 22E MIL-W-16878/4 .010 7/#30
7	6@16'	E22 GRAY	WIRE 22E MIL-W-16878/4 .010 7/#30
6	6@16'	E22 BROWN	WIRE 22E MIL-W-16878/4 .010 7/#30
5	6@16'	E22 BLUE 7 STR	WIRE 22E MIL-W-16878/4 .010 7/#30
4	6@16'	E22 WHT/RED	WIRE 22E MIL-W-16878/4 .010 7/#30
3	A/R	PAVE-Seal 80	EPOXY BLACK
2	1	NOR-CAL #G-275	GASKET COPPER (NOT SHOWN)
1	1	CF275-SS	HOUSING CF275-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses
CF275-SS-80-60-TE22-96-96

PART NUMBER

2427

PROJECTION

