



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-7} CC/S.
2. HYPOT 630 VDC 500 MEGAOHMS MINIMUM 0.01 SECOND MINIMUM CENTER CONDUCTOR TO HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
5. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON ATMOSPHERE SIDE OF HOUSING.

5	A/R	SUPER O-LUBE	LUBRICANT SILICONE-BASED
4	1	-905 VITON	O-RING -905 VITON 75
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	1	2616PG2C	ROD BRASS THREADED 10-32 1.67"L
1	1	5P50N-SS	HOUSING SO8-SS PARKER
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 XX DECIMAL ±0.1 XXX DECIMAL ±0.02 XXXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, OH 45414-2445
 U.S.A.
 Tel: (937) 890-1100
 Fax: (937) 890-5165
 www.pavetechnologyco.com

PAVE technology co.

01346@prian

SO8-SS-80-E-1-B10.32-.5-.5

Part Number: **2616**

Revision: -

PECORATION