



NOTES:

1. HIPOT 2500 VAC: 5 mA MAX LEAKAGE FROM CENTER CONDUCTOR TO SHELL.

4	1	TIN COPPER #20	WIRE BUS #20 TINNED
3	1	AMPH# 10400	PLUG MHVST JCK BHD REC
2	2.5g	TRA-BOND F202	EPOXY CLEAR
1	1	U-SWTT-20	TUBING TEFLON 0.034 SEMI FLEXIBLE 0.016
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE #0.5  
 XX DECIMAL ±0.1 XXX DECIMAL ±0.02 XXXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

	2751 Thundehawk Court Dayton, OH 45414-3445 U.S.A. tel (937) 890-1100 fax (937) 8905165 www.pave-technology.co.com	
	DESCRIPTION <b>VSBNC-SS-200-1-CRTFE18-BNC-13</b>	
PART NUMBER <b>2628</b>	REVISION LEVEL <b>A</b>	PROJECTION 