



NOTES:

1. HE LEAK TEST @1 ATM. <math>10^{-5}</math> CC/S.
2. HYPOT 630 VDC 500 MEGAOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE.
3. OPTICAL CONTINUITY TEST ON FIBER.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).

8	1	PC20 UL1569 WHT	WIRE 20PVC UL1569 .016 7/#28
7	1	PC20 UL1569 RED	WIRE 20PVC UL1569 .016 7/#28
6	1	PC20 UL1569 GRN	WIRE 20PVC UL1569 .016 7/#28
5	1	PC20 UL1569 BLK	WIRE 20PVC UL1569 .016 7/#28
4	1	-016 VITON	O-RING -016 VITON 75
3	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE-BASED
2	1	D288M1FISP	PATCHCORD FIBER OPTIC 1m ST-ST MULTIMODE
1	1	0130	HOUSING SPF12-E
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 SPF12-E-80-4/1-PC20/MMFOST-12-12

PART NUMBER  
 2649

REVISION LEVEL  
 C

PROJECTION