



**NOTES:**

1. LEAK TEST: 325 PSI, NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & SHIELD.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.

5	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED
4	1	-325 VITON	O-RING -325 VITON 75
3	42	TEF 2/C #28 TSP	CABLE #28 TSJP 3-4 TWIST
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0324 SP26	HOUSING SP26-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microninch RMS

**PAVE technology** 2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pave technology.com

DESCRIPTION PAVE-Seal® Cable Harnesses  
**SP26-E-150-42TSP-TE28-36-36**

PART NUMBER **2722**

REVISION LEVEL

PROJECTION