



2728	MS27467T23F35P	MS27466T23F35S	KT11553-8
2728A	MS27467T23F35PA	MS27466T23F35SA	KT11553-9
2728B	MS27467T23F35PB	MS27466T23F35SB	KT11553-10
2728C	MS27467T23F35PC	MS27466T23F35SC	KT11553-11
2728D	MS27467T23F35PD	MS27466T23F35SD	KT11553-12
PART#	ITEM 1	ITEM 2	KAMAN#

NOTES:

1. HE LEAK TEST @1 ATM. 5×10^{-8} CC/S.
2. HYPOT 630 VDC 500 MEGAOHMS MINIMUM 0.01 SECOND MINIMUM PIN TO PIN AND HOUSING.
3. CONTINUITY TEST W/ MATING CONNECTORS 0.5 OHMS.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
6. REF-OPERATING TEMPERATURE: -25 TO 125 °C
7. SHELLS FOR ITEMS 1 & 2, AND HOUSING (ITEM 3) TO HAVE ELECTRICAL CONTINUITY.

6	1	0185	NUT VS26-SS
5	A/R	PAVE-Seal 150	EPOXY BLACK
4	1	-226 VITON	O-RING -226 VITON 75
3	1	1531	HOUSING VS26-SS
2	1	SEE TABLE	RCPT 100#22 SOCKETS
1	1	SEE TABLE	PLUG 100#22 PINS
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
VS26-SS-150-100-22-27466PS

PART NUMBER
2728

REVISION LEVEL
C

PROJECTION