



USE TRUARC N5000-50 RETAINING RING OR EQUAL.
IF REMOVED FROM PORT, REPLACE O-RINGS.

NOTES:

1. LEAK TEST: 1450 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 1000 VAC 500 mA MAXIMUM LEAKAGE, 1 SEC WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. DIMENSIONS ARE IN INCHES [MILLIMETERS].
7. WIRE POSITIONS ARE APPROXIMATE AND VARIABLE.

8	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED
7	2	-012 VITON	O-RING -012 VITON 75
6	A/R	PAVE-Seal 150	EPOXY BLACK
5	1	PC18 UL1569 WHT	WIRE 18PC UL1569 .016 7/#26
4	1	PC18 UL1569 RED	WIRE 18PC UL1569 .016 7/#26
3	1	PC18 UL1569 BLU	WIRE 18PC UL1569 .016 7/#26
2	1	PC18 UL1569 BLK	WIRE 18PC UL1569 .016 7/#26
1	1	1226 SP8L	HOUSING SP8L-E
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal Cable Harnesses
 SP8L-E-150-4-PC18-150CM-150CM

PART NUMBER
 2770

REVISION LEVEL
 A
 PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS