



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 4 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGAOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
5. VOIDS SMALLER THAN $\phi 0.035$ ARE ACCEPTABLE.
6. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON EACH SIDE OF HOUSING.
7. REF-OPERATING TEMPERATURE RANGE -20°C TO 150°C .

9	4	E30 YELLOW	WIRE 30AWG E TEFLON 7 STRAND
8	5	E30 WHITE	WIRE 30AWG E TEFLON 7 STRAND
7	5	E30 VIOLET	WIRE 30AWG E TEFLON 7 STRAND
6	5	E30 RED	WIRE 30AWG E TEFLON 7 STRAND
5	5	E30 ORANGE	WIRE 30AWG E TEFLON 7 STRAND
4	5	E30 GRAY	WIRE 30AWG E TEFLON 7 STRAND
3	5	E30 BROWN	WIRE 30AWG E TEFLON 7 STRAND
2	1	2920	HOUSING PT6H-SS (1.125 HEX)
1	1	PAVE-Seal 200HV	EPOXY BLUE
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS

PAVE technology co. 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
PT6H-SS-200HV-34-TE30-48-48

PART NUMBER
2879

REVISION LEVEL
B

PROJECTION