



NOTES:

1. LEAK TEST: 700 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. REF-OPERATING TEMPERATURE -25°C TO 200°C.
7. WIRE POSITIONS ARE APPROXIMATE AND VARIABLE.
8. ITEM 5 IS ENDSTRIPPED AND WELDED BY SUPPLIER.

5	6	5TC-TT-K-36-36	CABLE T/C TYPE K 36AWG TEFLON WELDED ENDS
4	1	EE22 MIL WHITE	WIRE 22EE MIL-W-16878/5 .015 7/#30
3	1	EE22 MIL RED	WIRE 22EE MIL-W-16878/5 .015 7/#30
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	0346	HOUSING PT8-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal@ Cable Harnesses
 PT8-SS-200-2/6P-TEE22/KT36-23.5/17-23.5/17

PART NUMBER
 2908

REVISION LEVEL A
 PROJECTION