



NOTES:

1. HE LEAK TEST @ 1 ATM 1×10^{-7} CC/SEC.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM PIN TO PIN AND HOUSING.
3. CONTINUITY TEST ALL CONDUCTORS WITH MATING CONNECTORS <math>< 0.5</math> Ohm PIN TO SOCKET.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).
6. VOIDS SMALLER THAN $\phi 0.035$ ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20°C TO 150°C .
8. MATING CONNECTORS PART#38999/46FJ35SN AND 38999/46FJ35PN: NOT SHIPPED W/ ASSEMBLY.

7	A/R	0185	NUT VS26-SS
6	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE-BASED
5	1	-226 VITON	O-RING -226 VITON 75
4	1	PAVE-Seal 150	EPOXY BLACK
3	1	40FJ35PN	RCPT 128 #22D PINS 999 SERIES IV
2	1	40FJ35SN	RCPT 128 #22D SOCKETS 999 SERIES IV
1	1	1531	HOUSING VS26-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 VS26-SS-150-128-22-40FJ35SP

PART NUMBER
 2936

REVISION LEVEL
 A
 PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS