



NOTES:

1. HE LEAK TEST @1 ATM.  $10 \times 10^{-9}$  CC/S OR LESS.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS LARGER THAN  $\phi.035$  ARE ACCEPTABLE.
7. REF OPERATING TEMPERATURE  $-20^{\circ}\text{C}$  TO  $150^{\circ}\text{C}$ .

5	1	0199	NUT VS22-SS (316SS)
4	1	-224 VITON	O-RING -224 VITON 75
3	25	NT20	CABLE T/C TYPE N 20AWG TEFLON
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0189/304SS	HOUSING VS22-304SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

**PAVE technology co.**

DESCRIPTION PAVE-Seal Cable Harnesses  
**VS22-SS-150-25P-NT20-36-36**

PART NUMBER **3212**

REVISION LEVEL -

PROJECTION