



NOTES:

1. HE LEAK TEST @ 1 ATM 10X10⁻⁸ CC/SEC OR LESS.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM PIN TO PIN AND HOUSING.
3. CONTINUITY TEST ALL CONDUCTORS WITH MATING CONNECTORS < 0.5 Ohm PIN TO SOCKET.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. VOIDS SMALLER THAN $\phi 0.035$ ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20°C TO 125°C.
8. MATING CONNECTORS NOT SHIPPED W/ ASSEMBLY.
9. A LETTER AFTER THE PAVE PART NUMBER (eg. 3244A) INDICATES ALTERNATE CLOCKING ON THE RECEPTACLES (SEE TABLE).

3244A	40FE35SA	46FE35PA	40FE35PA	46FE35SA
3244	40FE35SN	46FE35PN	40FE35PN	46FE35SN
PAVE#	ITEM 2	(MATE)	ITEM 3	(MATE)

6	A/R	0185	NUT VS26-SS
5	1	-226 VITON	O-RING -226 VITON 75
4	1	PAVE-Seal 150	EPOXY BLACK
3	1	SEE TABLE	RCPT 55 #22 PIN 999 SERIES IV
2	1	SEE TABLE	RCPT 55 #22 SOCKET 999 SERIES IV
1	1	1531	HOUSING VS26-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION: VS26-SS-150-55-22-40FE35SP*(NP)

PART NUMBER (SEE TABLE): **3244***

REVISION LEVEL: **A**

PROJECTION:

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS