



NOTES:

1. HE LEAK TEST VACUUM 10×10^{-8} CC/SEC OR LESS.
2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
3. ALL PARTS MUST PASS ALL TESTS.
4. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN $\phi 0.035$ ARE ACCEPTABLE ON ALL OTHER SURFACES.
5. REF-OPERATING TEMPERATURE -20°C TO 125°C .
6. 3281 USES ITEM 3 & 3281-1 USES ITEM 4.
7. MAXIMUM TEMPERATURE ALLOWED: 125°C .

4	1	NOVELX 20X1.12	FLEX CABLE 20 X 1.12
3	1	NOVELX10.5X1.12	FLEX CABLE 10.5 X 1.12
2	1	-021 VITON	O-RING -021 VITON 75
1	A/R	PAVE-Seal 150	EPOXY BLACK
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 SP24/6.2-E-150-1-FLEX

PART NUMBER
3281

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS