



NOTES:

1. HE LEAK TEST VACUUM 10X10⁻⁷ CC/SEC OR LESS.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM PIN TO PIN AND HOUSING WITH MATING PLUGS.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. VOIDS LARGER THAN Ø.035 [.89] ARE NOT ACCEPTABLE.
6. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
7. DIMENSIONS ARE INCHES [millimeters].

| 6 | 1 | 0199 | NUT VS22-SS (316SS) |
|------|-----|---------------|---------------------------|
| 5 | 1 | -224 VITON | O-RING -224 VITON 75 |
| 4 | A/R | PAVE-Seal 150 | EPOXY BLACK |
| 3 | 1 | SEE TABLE | RCPT 32#20 SOC SERIES III |
| 2 | 1 | SEE TABLE | RCPT 32#20 PIN SERIES III |
| 1 | 1 | 0189/304SS | HOUSING VS22-SS |
| ITEM | QTY | PART NUMBER | DESCRIPTION |

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

| | |
|--------------------------------|----------------|
| DESCRIPTION | |
| VS22-SS-150-32-20-99920PS (NP) | |
| PART NUMBER | MATERIAL NOTED |
| 3332* | A |
| REVISION LEVEL | PROJECTION |
| | ⊙ ◻ |

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS