



20	1	PC26 YELLOW	WIRE 26PVC UL1007/UL1569 .016 7/#34	16	1	PC26 BROWN	WIRE 26PVC UL1007/UL1569 .016 7/#34
19	1	PC26 WHITE	WIRE 26PVC UL1007/UL1569 .016 7/#34	15	1	PC26 BLUE	WIRE 26PVC UL1007/UL1569 .016 7/#34
18	1	PC26 RED	WIRE 26PVC UL1007/UL1569 .016 7/#34	14	1	PC26 BLACK	WIRE 26PVC UL1007/UL1569 .016 7/#34
17	1	PC26 GRAY	WIRE 26PVC UL1007/UL1569 .016 7/#34	13	1	PC26 WHT/YLW	WIRE 26PVC UL1007/UL1569 .016 7/#34
ITEM	QTY	PART NUMBER	DESCRIPTION	ITEM	QTY	PART NUMBER	DESCRIPTION

NOTES:

1. LEAK TEST: 30 PSI, NO BUBBLES 4 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING & COLOR ARRANGEMENT IS APPROXIMATE & VARIABLE.
6. VOIDS LARGER THAN $\phi .035$ [.89] ARE NOT ACCEPTABLE.
7. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON ATMOSPHERE SIDE OF HOUSING.
8. REF-OPERATING TEMPERATURE 0°C TO 80°C.
9. DIMENSIONS ARE INCHES [millimeters].

12	1	PC26 WHT/VIO	WIRE 26PVC UL1007/UL1569 .016 7/#34
11	1	PC26 WHT/BRN	WIRE 26PVC UL1007/UL1569 .016 7/#34
10	1	PC26 WHT/BLU	WIRE 26PVC UL1007/UL1569 .016 7/#34
9	1	PC22 WHT/RED	WIRE 22PVC UL1007/UL1569 .016 7/#30
8	1	PC22 WHT/GRN	WIRE 22PVC UL1007/UL1569 .016 7/#30
7	1	PC20 UL1569 VIO	WIRE 20PVC UL1007/UL1569 .016 7/#28
6	1	PC20 BLK/WHT	WIRE 20PVC UL1007/UL1569 .016 7/#28
5	1	70576	CABLE USB 2.0 MALE TYPE A TO TYPE B 5-WIRE 12" BLACK ROHS
4	A/R	PAVE-Seal 150	EPOXY BLACK
3	1	CONXALL 4291	NUT HEX
2	1	CONXALL 4293	GASKET NYLON
1	1	3481	HOUSING CONXALL PANEL MOUNT
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
CONXALL-150-2/2/11/1-PC20/22/26/USB-24-24

PART NUMBER
3472

MATERIAL NOTED

REVISION LEVEL
E

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS