



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, SOLDER CUPS TO HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. NO VOIDS LARGER THAN  $\phi.035$  [.89] ARE ACCEPTABLE.
6. DIMENSIONS ARE INCHES [millimeters].
7. REF-OPERATING TEMPERATURE RANGE  $-20^{\circ}\text{C}$  TO  $150^{\circ}\text{C}$ .

4	1	1485	SOLDER CUP #20 GOLD PLATED
3	1	3387	SOLDER CUP #20 & SMALLER
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	3354	HOUSING PT4-B
ITEM	QTY	PART#	DESCRIPTION



DESCRIPTION	PAVE-Mate® I Connectors	
PART NUMBER	PT4-B-200-1-20-SC-SC	
REVISION LEVEL	3550	
PROJECTION	A	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS