



**NOTES:**

1. HE LEAK TEST VACUUM  $10 \times 10^{-7}$  CC/SEC OR LESS. LEAK TEST IS PERFORMED USING A G-275 VITON GASKET.
2. HYPOT 630 VDC 500 MΩ MINIMUM .01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE COLOR POSITIONING IS VARIABLE.
6. VOIDS LARGER THAN  $\phi .035$  [.89] ARE NOT ACCEPTABLE.
7. REF-OPERATING TEMPERATURE  $-59^{\circ}\text{C}$  TO  $120^{\circ}\text{C}$ .
8. DIMENSIONS ARE INCHES [millimeters].

13	1	GASKET G-275 C	GASKET COPPER
12	6	E26 YELLOW	WIRE 26E MIL-W-16878/4 7/#34
11	6	E26 WHT/RED	WIRE 26E MIL-W-16878/4 7/#34
10	6	E26 WHT/BLK	WIRE 26E MIL-W-16878/4 7/#34
9	6	E26 WHITE	WIRE 26E MIL-W-16878/4 7/#34
8	6	E26 RED	WIRE 26E MIL-W-16878/4 7/#34
7	6	E26 ORG/WHT	WIRE 26E MIL-W-16878/4 7/#34
6	6	E26 GREEN	WIRE 26E MIL-W-16878/4 7/#34
5	6	E26 GRAY	WIRE 26E MIL-W-16878/4 7/#34
4	6	E26 BROWN	WIRE 26E MIL-W-16878/4 7/#34
3	6	E26 BLUE	WIRE 26E MIL-W-16878/4 7/#34
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1473	HOUSING CF275-SS
<b>ITEM</b>	<b>QTY</b>	<b>PART NUMBER</b>	<b>DESCRIPTION</b>

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 CF275-SS-150-60-TE26-96-96

PART NUMBER  
**3553**

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEGREE SURFACE FINISH 128 microinch RMS