



PAVE#	X
3553	96 [2438]
3553-1	120 [0348]



NOTES:

1. HE LEAK TEST @ 1 ATM. 1×10^{-6} CC/SEC OR LESS. LEAK TEST IS PERFORMED USING A G-275 VITON GASKET, A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & COLOR POSITIONS ARE VARIABLE.
6. COSMETIC SURFACE VOIDS NOT ON O-RING SEALING SURFACES ARE ACCEPTABLE BASED ON THE SEAL'S DIAMETER:
 $\leq .5$ [12.7] SEAL DIAMETER: $\phi .035$ [.89] MAX ALLOWED VOID SIZE
 $> .5$ [12.7] SEAL DIAMETER: $\phi .060$ [1.5] MAX ALLOWED VOID SIZE
7. REF-OPERATING TEMPERATURE -59°C TO 120°C .
8. DIMENSIONS ARE INCHES [millimeters].
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

13	1	GASKET G-275 C	GASKET COPPER
12	6	E26 YELLOW	WIRE 26E MIL-W-16878/4 7/#34
11	6	E26 WHT/RED	WIRE 26E MIL-W-16878/4 7/#34
10	6	E26 WHT/BLK	WIRE 26E MIL-W-16878/4 7/#34
9	6	E26 WHITE	WIRE 26E MIL-W-16878/4 7/#34
8	6	E26 RED	WIRE 26E MIL-W-16878/4 7/#34
7	6	E26 ORG/WHT	WIRE 26E MIL-W-16878/4 7/#34
6	6	E26 GREEN	WIRE 26E MIL-W-16878/4 7/#34
5	6	E26 GRAY	WIRE 26E MIL-W-16878/4 7/#34
4	6	E26 BROWN	WIRE 26E MIL-W-16878/4 7/#34
3	6	E26 BLUE	WIRE 26E MIL-W-16878/4 7/#34
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1473	HOUSING CF275-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 CF275-SS-150-60-TE26-96-X

PART NUMBER
3553

MATERIAL NOTED

REVISION LEVEL
 A

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE. SURFACE FINISH 128 microinch RMS