



**NOTES:**

1. LEAK TEST: 750 PSI, NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE COLOR POSITIONS ARE VARIABLE.
6. VOIDS LARGER THAN  $\phi .035$  [.89] ARE NOT ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20°C TO 125°C.
8. DIMENSIONS ARE INCHES [millimeters].

8	3	E14 YELLOW	WIRE 14E MIL-W-16878/4 .012 19/#27
7	3	E14 WHITE	WIRE 14E MIL-W-16878/4 .012 19/#27
6	3	E14 RED	WIRE 14E MIL-W-16878/4 .012 19/#27
5	3	E14 ORANGE	WIRE 14E MIL-W-16878/4 .012 19/#27
4	3	E14 BLUE	WIRE 14E MIL-W-16878/4 .012 19/#27
3	4	E14 BLACK	WIRE 14E MIL-W-16878/4 .012 19/#27
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1625	HOUSING PT16-B
ITEM	QTY	PART NUMBER	DESCRIPTION

**PAVE technology co.**  
 2751 Thunderhawk Court  
 Dayton, OH 45414-3445  
 U.S.A.  
 tel (937) 890-1100  
 fax (937) 8905165  
 www.pavetechnologyco.com

DESCRIPTION  
 PT16-B-150-19-TE14-48-48

PART NUMBER  
**3621**

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS