



NOTES:

1. HE LEAK TEST @ 1ATM 10X10⁻⁷ CC/SEC OR LESS.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM CONDUCTOR TO CONDUCTOR AND HOUSING WITH MATING CONNECTORS.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. PAVE 3653 DOES NOT INCLUDE ITEMS 8 & 9. PAVE 3653-1 INCLUDES ITEMS 8 & 9. REF-ITEM 8 CAN BE INSTALLED ON STRANDED Cat 5e CABLE WITH STANDARD RJ45 MODULAR PLUG TERMINATION TOOLING.
6. COSMETIC SURFACE VOIDS SMALLER THAN ϕ .035 [.89] ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE RANGE -20°C TO 80°C.
8. DIMENSIONS ARE INCHES [millimeters].
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
10. INSTALLED PART IS HERMETICALLY SEALED AT THE BULKHEAD WITH OR WITHOUT THE MATING CONNECTORS ATTACHED.
11. WHEN USED WITH A PROPERERLY RATED CAP OR CABLE ON THE ATMOSPHERE SIDE, THE CONNECTOR MAINTAINS AN IP67 ENVIRONMENTAL RATING.
12. WHEN INSTALLING A CAP OR PLUG ON THE ABS THREADS (ATMOSPHERE SIDE), HAND TIGHTEN ONLY.

9	1	65-0300	*SEE NOTES 5, 11, & 12	CAP PROTECTIVE PA6 NYLON GF IP67
8	1	ENQAM315	*SEE NOTES 5, 11, & 12	PLUG RJ45 MALE IP67 FIELD INSTALLABLE
7	1	3671		NUT VS15FP-B
6	1	-024 VITON		O-RING -024 VITON 75
5	1	-		O-RING WJP1F5 NITRILE
4	1	-		HOUSING WJP1F5 ABS THREADS
3	1	WJP1F5		CONNECTOR RJ45 CAT5 SHIELDED (2X) MOUNTED TO PCB
2	A/R	PAVE-Seal 150		EPOXY BLACK
1	1	3670		HOUSING VS15FP-AL ANODIZED MIL-A-8625 TYPE-II CLASS-2 (BLACK)
ITEM	QTY	PART NUMBER		DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION VS15FP-AL-150-8-24-RJ45-RJ45	
PART NUMBER 3653	MATERIAL NOTED REVISION LEVEL G
PROJECTION ☉	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
 X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS