



NOTES:

1. HE LEAK TEST VACUUM 10×10^{-7} CC/SEC OR LESS. LEAK TEST IS PERFORMED USING A G-275 VITON GASKET.
2. HYPOT 630 VDC 500 MΩ MINIMUM .01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. BOTH SIDOS OF ITEM 3 WILL BE MARKED WITH CORRESPONDING NUMBERS OR LETTERS.
4. MINIMUM QTY 50 OF ITEM 3 REQUIRED.
5. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
6. ALL PARTS MUST PASS ALL TESTS.
7. VOIDS LARGER THAN $\phi .035$ [.89] ARE NOT ACCEPTABLE.
8. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
9. DIMENSIONS ARE INCHES [millimeters].

5	1	GASKET G-275 C	GASKET COPPER
4	A/R	-	BRADY WIRE MARKERS
3	52	ET24-SLE	CABLE T/C TYPE E#24 TEFLON SLE
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1473	HOUSING CF275-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
CF275-SS-150-50P-ET24-18-36

PART NUMBER

3666

MATERIAL NOTED

REVISION LEVEL A

PROJECTION



ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS