



NOTES:

1. HE LEAK TEST VACUUM 10×10^{-7} CC/SEC OR LESS. LEAK TEST IS PERFORMED USING A G-275 VITON GASKET.
2. HYPOT 630 VDC 500 MΩ MINIMUM .01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. WIRES TO BE TWISTED INTO PAIRS, EACH PAIR CONSISTING OF 1 EACH OF ITEMS 3 & 4.
4. EACH TWISTED PAIR SHALL HAVE A PIECE OF ITEM 5 SHRUNK ON BOTH SIDES AND MARKED WITH CORRESPONDING NUMBERS OR LETTERS.
5. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
6. ALL PARTS MUST PASS ALL TESTS.
7. VOIDS LARGER THAN $\phi .035$ [.89] ARE NOT ACCEPTABLE.
8. REF-OPERATING TEMPERATURE -20°C TO 125°C .
9. DIMENSIONS ARE INCHES [millimeters].

7	1	GASKET G-275 C	GASKET COPPER
6	A/R	-	BRADY WIRE MARKERS
5	90	M23053/18-205-C	TUBING HEAT SHRINK KYNAR .187
4	45	E24 WHITE	WIRE 24E MIL-W-16878/4 7/#32
3	45	E24 BROWN	WIRE 24E MIL-W-16878/4 7/#32
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1473	HOUSING CF275-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 CF275-SS-150-45TP-E24-18-36

PART NUMBER
3668

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS